

Vxxx-13.5-12 Models		V650	V675	V700	V725	V750
Electrical						
Input						
Maximum voltage per input ¹	V	750	750	750	750	750
Maximum current (Imp) per input ²	A	12.3	12.3	12.3	12.3	12.3
Maximum short-circuit current (Isc) per input	A	13	13	13	13	13
MPP tracking voltage range	V	190 - 700	190 - 700	190 - 700	190 - 700	190 - 700
Startup voltage per input	V	400	400	400	400	400
Number of inputs		2	2	2	2	2
Output						
Output voltage range	V	0 - 650	0 - 675	0 - 700	0 - 725	0 - 750
Output voltage at full power	V	570	595	620	645	670
Output voltage at zero power	V	650	675	700	725	750
Maximum output current	A	12	12	12	12	12
Maximum continuous output power	kWdc	6.6	6.9	7.2	7.5	7.8
Efficiency (max / CEC / Euro)	%	99.5 / 99.3 / 99.2				
Mechanical						
Input & output connector	Amphenol H4					
Dimensions	10.71" x 8.66" x 3.94" (272 mm x 220 mm x 100 mm)					
Weight	9.0 lbs. (4.1 kg)					
Ambient temperature operating range	-40 °F to +122 °F (-40 °C to +50 °C)					
Cooling	Convection					
Environmental						
Environmental category	Outdoor					
Pollution degree	2					
Maximum operating altitude ³	9843 ft (3000 m)					
Overvoltage category	OVII					
Ingress protection	IP66 / 4X					
General						
Compliance	ETL to UL 1741; IEC 61000-6-1, 61000-6-3, 62109; CE; Giteki 2-1-19; FCC Part 15, class A					

1. Voc at coldest design temp. Follow Ampt's design guidelines to determine the number of modules per input and max. system voltage.

2. Maximum Imp of modules on the input at standard test condition (STC) - irradiation level of 1000 W/m² at 25°C.

3. Optimizer derates above this altitude.